




79G5 PCI/PCle Multifunction I/O Boards

PCle Multifunction I/O Board

The 79G5 is NAI's rugged single-slot, half-size PCIe multifunction I/O and communications board engineered for demanding aerospace, defense, and industrial applications. This board is ideally suited for high channel density and combined Multifunction I/O requirement systems. It can accommodate up to three NAI Configurable Open Systems Architecture™ (COSA®) smart function modules. By configuring the 79G5 with these modules, engineers can adapt the board's functionality to meet their unique needs, accelerating deployment for digital and analog I/O, position control, measurement/simulation, and communication interface applications.



Features

- Up to 3 independent smart I/O function modules supported
- Front high density rugged Micro-D I/O receptacle connector
- Independent internal x1 SerDes interface to each function module slot
- Continuous Background Built-in-Test (BIT)
- PCIe 2.0 (x1), (up to 5 GT/s)
- Single slot, full height, half-length PCIe 4.2" (107 mm) h x 6.6" (175 mm) l (env.)
- Low power dissipation (< 3.5 W (typical for motherboard) plus module power)
- Maintenance/Console interface includes:
 - 1x Gig-E, 1x RS-232 and 1x USB (pending)
 - Dedicated mini-HDMI type-C receptacle
- COSA® Architecture
- Intelligent NAI Brd I/O library and API support included
- Operating temp: 0° C to +70° C

Select up to 3 independent functions for your application

I/O Modules					
Function	Module	Description	Function	Module	Description
Analog-to-Digital	AD1	12 CH. A/D, ± 10 V, Dedicated, 256 kHz (max), Sigma-Delta	Digital-to-Analog	DA5	4 CH. D/A, High-Voltage/High-Current Half-Bridge (2 Channels Full-Bridge) External VCC Sourced Outputs
	AD2	12 CH. A/D, ± 100 V (max), Dedicated, 256 kHz (max), Sigma-Delta	Digital IO - Differential Transceiver	DF1	16 CH. Differential I/O, Input: -10 V to +10 V (422), -7 V to +12 V (485) Output: -25 V to +5 V
	AD3	12 CH. A/D, ± 25 mA, Dedicated, 256 kHz (max), Sigma-Delta		DF2	16 CH. 16 Channel Enhanced Differential I/O
	AD4	16 CH. A/D, ± 10 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR	Discrete IO - Multichannel, Programmable	DT1	24 CH. Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)
	AD5	16 CH. A/D, ± 50 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		DT2	16 CH. Discrete I/O, ± 80 V Input/Output, Max Iout 600 mA, Isolated/Ch Switch (out)
	AD6	16 CH. A/D, ± 100 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		DT3	4 CH. Discrete Hi & Lo Side Switch Output @ 65V/2A (max), external individual supplied VCC & VSS per channel pair
	ADE	16 CH. A/D, ± 10 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling		DT4	24 CH. Enhanced DT1
	ADF	16 CH. A/D, ± 100 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling		DT5	16 CH. Enhanced DT2
Chip Detector and Fuzz Burn	CD1	6 CH. Chip Detector (CD) and Fuzz Burn (FB)	Relay	RY1	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Non Latching
Digital-to-Analog	DA1	12 CH. D/A, ± 10 V, 25 mA Per Channel, Current or Voltage Control		RY2	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Latching
	DA2	16 CH. D/A, ± 10 V, 10 mA Per Channel, No Current Control	Digital IO - TTL/CMOS	TL1	24 CH. TTL I/O, Standard Functionality, Programmable
	DA3	4 CH. D/A, ± 40 V, ± 100 mA, Voltage or Current Output		TL2	24 CH. TTL I/O, Enhanced Functionality, Programmable
	DA4	4 CH. D/A, ± 20 to ± 80 , 10 mA, Voltage Control Only	Variable Reluctance	VR1	8 CH. Variable Reluctance Signal Input and General-Purpose Pulse Counter, ± 100 V, 100 kHz (max)
Measurement & Simulation Modules					
Function	Module	Description	Function	Module	Description
AC Reference	AC2	2 CH. AC Reference Source, 47 Hz - 20 KHz, $\pm 3\%$ Acc, 2 - 28 Vrms, 6 VA (Max/Ch) Power	LVDT RVDT Measurement and Simulation	LD5	4 CH. LVDT/RVDT to Digital, 28-90 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq
	AC3	2 CH. AC Reference Source, 47 Hz - 2.5 KHz, $\pm 3\%$ Acc, 28 - 115 Vrms, 6 VA (Max/Ch) Power	Synchro Resolver Measurement and Simulation	DSx (DRx)	1 - 3 CH. Digital to Synchro/Resolver, 2 - 90 VLL, 2 - 1115 Vrms Exc, 47 Hz - 20 kHz Freq
LVDT RVDT Measurement and Simulation	DLx	1 - 3 CH. Digital to LVDT/RVDT, 2 - 90 Vrms Full Scale, 2 - 115 Vrms Exc, 47 Hz - 20 kHz Freq		SDx	4 CH. Synchro/Resolver to Digital, 2 - 90 Vrms Input, 2 - 115 Vrms Exc, 47 Hz to 20 kHz Freq
	LD1	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq	Thermocouple and RTD Measurement	RT1	8 CH. Resistance Temperature Detectors (RTD), 2, 3, or 4 wire, 16 Bit Res, 16.7 Hz/Ch
	LD2	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 1 KHz - 5 KHz Freq		TC1	8 CH. Thermocouple, 4.17 - 470 Hz, ± 100 mV A/D
	LD3	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 5 KHz - 10 KHz Freq		TR1	8 CH. Thermocouple (TCx) & Resistance Temperature Detectors (RTD), programmable per channel
	LD4	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 10 KHz - 20 KHz Freq	Strain Gauge Measurement	SG1	4 CH. Strain Gauge, 4.7 Hz - 4.8 KHz, Measurement, Conventional 4-Arm Bridge

Communication Modules					
Function	Module	Description	Function	Module	Description
ARINC Communications	<u>AR1</u>	12 CH. ARINC 429, 100 KHz or 12.5 KHz, RX/TX, 256 Word Tx/Rx Buffer	MIL-STD-1553B	<u>FTE</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
	<u>AR2</u>	1 CH. ARINC 568 (CH-1, RX & TX) & 1 Channel ARINC 579 (CH-2, Programmable RX or TX), 1024-Word TX & RX Buffers per Ch.		<u>FTF</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
CANBus Communications	<u>CB1</u>	8 CH. CANBus, CAN 2.0 A/B, 16 K RX/TX Buffer, 1 Mb/s Max Data Rate	MIL-STD-1760	<u>FTJ</u>	1 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled
	<u>CB2</u>	8 CH. CANBus, J1939, 16 K RX/TX Buffer, 500 kb/s Max Data Rate		<u>FTK</u>	2 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled
	<u>CB3</u>	8 CH. CANBus, CAN 2.0 A/B (CB1) or J1939 (CB2) protocol layer programmable per channel	Serial Communications	<u>SC1</u>	4 CH. Serial, RS-232/422/423 (MIL-STD-188C)/485, Non Isolated
MIL-STD-1553B	<u>FTA</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled		<u>SC3</u>	8 CH. (max) RS-232/422/485 Serial Communications or GPIO, Programmable, Non-isolated
	<u>FTB</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled		<u>SC5</u>	4 CH. RS-232/422/485 communications, isolated per channel and from SYS GND
	<u>FTC</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled		<u>SC6</u>	4 CH. RS-232/422/485 communications, individual SYS GND provided per channel (non-isolated)
	<u>FTD</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Direct Coupled			
Storage					
Function	Module	Description	Function	Module	Description
SATA Solid State Drive (SSD)	<u>FM2</u>	1 CH. 480 GB MLC SATA Flash, extended temp -40°C to 85°C operation			
Combination Modules					
Function	Module	Description	Function	Module	Description
Combo	<u>CM5</u>	2 CH. Dual-redundant MIL-STD-1553 & 8 Channel ARINC 429/575, 100 KHz or 12.5 KHz, RX or TX, 256 Word Tx/Rx Buffer	Combo	<u>CM8</u>	2 CH. Dual-redundant MIL-STD-1553 & 12 Channel Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)

Architected for Versatility

NAI's Configurable Open Systems Architecture™ (COSA®) offers a choice of over 100 smart I/O, communications, or Ethernet switch functions, providing the highest packaging density and greatest flexibility of ruggedized embedded product solutions in the industry. Preexisting, fully-tested functions can be combined in an unlimited number of ways quickly and easily.

One-Source Efficiencies

Eliminate man-months of integration with a configured, field-proven system from NAI. Specification to deployment is a seamless experience as all design, state-of-the-art manufacturing, assembly and test are performed - by one trusted source. All facilities are located within the U.S. and optimized for high-mix/low volume production runs and extended lifecycle support.

Product Lifecycle Management

From design to production and beyond, NAI's product lifecycle management strategy ensures the long-term availability of COTS products through configuration management, technology refresh and obsolescence component purchase and storage.

All specifications are subject to change without notice. All product and company names are trademarks or registered trademarks of their respective holders

