




NIU3E Rugged COTS Systems

Rugged Embedded Multifunction I/O System with 10 GB Fiber Optic & 1 GB Copper Ethernet Switch

The NIU3E is a small, rugged, low-power, self-contained multifunction I/O processing system preconfigured with 24-CH programmable Discrete I/O, 8-CH ARINC 429/575, 4-CH CANBus and 2-CH MIL-STD-1553 functions and incorporates an Ethernet switch module that offers four (4) 10GBase-SR multimode fiber optic ports and sixteen (16) 10/100/1000Base-T Ethernet ports. The NIU3E can also be configured with two smart Configurable Open Systems Architecture™ (COSA®) function modules. The NIU3E boasts a Dual or Quad Core ARM A53 processor for customer application and I/O and communications management. The NIU3E is configured with two 10/100/1000Base-T (GbE) Ethernet ports and an RS-232 port for maintenance / diagnostic or configuration interface. Ideally suited for rugged Mil-Aero applications, the NIU3E delivers off-the-shelf solutions that accelerate deployment of SWaP-optimized systems in air, land and sea applications.

The NIU3E rugged multifunction I/O and communications processing platform provides scalable system level solutions enabling networks including on-board vehicle, marine and aircraft platforms, to field and expand digital network architectures for network-centric operations.



Features

- Preconfigured Onboard I/O Functions**
 - 24-CH Discrete I/O (Enhanced Mode Optional)
 - 8-CH ARINC 429/575
 - 4-CH CAN bus; CAN A/B 2.0, CAN-FD, ARINC-825
 - 2-CH MIL-STD-1553
- Supports Two NAI smart I/O function modules**
 - 100+ modules to choose from Customer-configurable COSA® architecture
- Minimized SWaP Footprint**
 - 7.2" x 7.1" x 3.2" (est.) (incl. connectors)
 - ~7.7 lbs.
 - 28 VDC @ ~0.675 A (est.) + Module Power
- Xilinx® Zynq® UltraScale+™ SoC with Dual/Quad Core ARM® Cortex® -A53 MPCore™ @ 1.2 GHz (max)**
 - 8 GB DDR4 RAM
 - 32 GB SATA Flash
- Supports ES2 Managed Switch Module**
 - 16x 10/100/1000Base-T (GbE)
 - 4x 10GBase-SR Fiber
 - 1x RS-232 debug port
- Connectivity**
 - 1x RS-232 debug port
 - 1x USB 2.0
- Power Supply Hold-up (Optional)**
 - 50+ milliseconds of Holdup time
- Certifiable**
 - DO-178C & DO-254 DALA (Contact Factory)
- Cybersecurity & Anti-Tamper**
 - FIPS-140-3 Level 3 (Contact Factory)
- Continuous Background BIT**
- Operating System Support**
 - Wind River® Helix™ Virtualization Platform, Wind River® Linux, VxWorks®, VxWorks® Cert Edition, Xilinx PetaLinux, DDC-I Deos™
- Rugged applications***
 - MIL-STD-810
 - MIL-STD-461
 - Operating temp: -40°C to +71°C
 - Conduction-cooled and Convection/Air-cooled options (contact factory)

*Designed to meet. Characterizations pending. EMI/EMC requires shielded cables and proper grounding practices.

Select up to 3 independent functions for your application

I/O Modules					
Function	Module	Description	Function	Module	Description
Analog-to-Digital	<u>AD1</u>	12 CH. A/D, ± 10 V, Dedicated, 256 kHz (max), Sigma-Delta	Digital IO - Differential Transceiver	<u>DF1</u>	16 CH. Differential I/O, Input: -10 V to +10 V (422), -7 V to +12 V (485) Output: -.25 V to +5 V
	<u>AD2</u>	12 CH. A/D, ± 100 V (max), Dedicated, 256 kHz (max), Sigma-Delta		<u>DF2</u>	16 CH. 16 Channel Enhanced Differential I/O
	<u>AD3</u>	12 CH. A/D, ± 25 mA, Dedicated, 256 kHz (max), Sigma-Delta	Discrete IO - Multichannel, Programmable	<u>DT1</u>	24 CH. Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)
	<u>AD4</u>	16 CH. A/D, ± 10 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		<u>DT2</u>	16 CH. Discrete I/O, ± 80 V Input/Output, Max Iout 600 mA, Isolated/Ch Switch (out)
	<u>AD5</u>	16 CH. A/D, ± 50 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		<u>DT3</u>	4 CH. Discrete Hi & Lo Side Switch Output @ 65V/2A (max), external individual supplied VCC & VSS per channel pair
	<u>AD6</u>	16 CH. A/D, ± 100 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		<u>DT4</u>	24 CH. Enhanced DT1
	<u>AD7</u>	16 CH. A/D, ± 10 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling	<u>DT5</u>	16 CH. Enhanced DT2	
<u>AD8</u>	16 CH. A/D, ± 100 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling	Relay	<u>RY1</u>	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Non Latching	
Chip Detector and Fuzz Burn	<u>CD1</u>		6 CH. Chip Detector (CD) and Fuzz Burn (FB)	<u>RY2</u>	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Latching
Digital-to-Analog	<u>DA1</u>	12 CH. D/A, ± 10 V, 25 mA Per Channel, Current or Voltage Control	Digital IO - TTL/CMOS	<u>TL1</u>	24 CH. TTL I/O, Standard Functionality, Programmable
	<u>DA2</u>	16 CH. D/A, ± 10 V, 10 mA Per Channel, No Current Control		<u>TL2</u>	24 CH. TTL I/O, Enhanced Functionality, Programmable
	<u>DA3</u>	4 CH. D/A, ± 40 V, ± 100 mA, Voltage or Current Output	Variable Reluctance	<u>VR1</u>	8 CH. Variable Reluctance Signal Input and General-Purpose Pulse Counter, ± 100 V, 100 kHz (max)
	<u>DA4</u>	4 CH. D/A, ± 20 to ± 80 , 10 mA, Voltage Control Only			

Measurement & Simulation Modules					
Function	Module	Description	Function	Module	Description
AC Reference	<u>AC2</u>	2 CH. AC Reference Source, 47 Hz - 20 KHz, $\pm 3\%$ Acc, 2 - 28 Vrms, 6 VA (Max/Ch) Power	LVDT RVDT Measurement and Simulation	<u>LD5</u>	4 CH. LVDT/RVDT to Digital, 28-90 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq
	<u>AC3</u>	2 CH. AC Reference Source, 47 Hz - 2.5 KHz, $\pm 3\%$ Acc, 28 - 115 Vrms, 6 VA (Max/Ch) Power		<u>RT1</u>	8 CH. Resistance Temperature Detectors (RTD), 2, 3, or 4 wire, 16 Bit Res, 16.7 Hz/Ch
LVDT RVDT Measurement and Simulation	<u>LD1</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq	Thermocouple and RTD Measurement	<u>TC1</u>	8 CH. Thermocouple, 4.17 - 470 Hz, ± 100 mV A/D
	<u>LD2</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 1 KHz - 5 KHz Freq		<u>TR1</u>	8 CH. Thermocouple (TCx) & Resistance Temperature Detectors (RTD), programmable per channel
	<u>LD3</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 5 KHz - 10 KHz Freq	Strain Gauge Measurement	<u>SG1</u>	4 CH. Strain Gauge, 4.7 Hz - 4.8 KHz, Measurement, Conventional 4-Arm Bridge
	<u>LD4</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 10 KHz - 20 KHz Freq			

Communication Modules

Function	Module	Description	Function	Module	Description
ARINC Communications	<u>AR1</u>	12 CH. ARINC 429, 100 KHz or 12.5 KHz, RX/TX, 256 Word Tx/Rx Buffer	MIL-STD-1553B	<u>FTE</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
	<u>AR2</u>	1 CH. ARINC 568 (CH-1, RX & TX) & 1 Channel ARINC 579 (CH-2, Programmable RX or TX), 1024-Word TX & RX Buffers per Ch.		<u>FTF</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
CANBus Communications	<u>CB1</u>	8 CH. CANBus, CAN 2.0 A/B, 16 K RX/TX Buffer, 1 Mb/s Max Data Rate	MIL-STD-1760	<u>FTJ</u>	1 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled
	<u>CB2</u>	8 CH. CANBus, J1939, 16 K RX/TX Buffer, 500 kb/s Max Data Rate		<u>FTK</u>	2 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled
	<u>CB3</u>	8 CH. CANBus, CAN 2.0 A/B (CB1) or J1939 (CB2) protocol layer programmable per channel	Serial Communications	<u>SC1</u>	4 CH. Serial, RS-232/422/423 (MIL-STD-188C)/485, Non Isolated
Ethernet NIC Interface	<u>EM1</u>	2 CH. Dual Ethernet I/F, Intel 82850, 10/100/1000		<u>SC3</u>	8 CH. (max) RS-232/422/485 Serial Communications or GPIO, Programmable, Non-isolated
Ethernet Switch	<u>ES2</u>	16 CH. (Ports) (max.) Ethernet Switch, 10/100/1000Base-T (GbE), 4 x Fiber Optic Ports (opt.), Layer 2+3 Managed		<u>SC5</u>	4 CH. RS-232/422/485 communications, isolated per channel and from SYS GND
MIL-STD-1553B	<u>FTA</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled		<u>SC6</u>	4 CH. RS-232/422/485 communications, individual SYS GND provided per channel (non-isolated)
	<u>FTB</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled	Time-Triggered Ethernet	<u>TE2</u>	1 CH. Tri-Redundant TTE/A664p7/AFDX/Best Effort End System
	<u>FTC</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled	Time Sensitive Networking	<u>TN1</u>	1 CH. Single Channel, Tri-Redundant Ports, TSN, IEEE 802.1AS, End Point, DornerWorks IP
	<u>FTD</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Direct Coupled			

Storage

Function	Module	Description	Function	Module	Description
SATA Solid State Drive (SSD)	<u>FM2</u>	1 CH. 480 GB MLC SATA Flash, extended temp -40°C to 85°C operation	SATA Solid State Drive (SSD)	<u>FM8</u>	1 CH. 1 TB SATA TLC NAND Flash, Extended Temperature Operation
	<u>FM7</u>	1 CH. 1 TB SATA Flash, 3D NAND MLC, 0-70 °C operation		<u>FM9</u>	1 CH. 1.92 TB SATA TLC NAND Flash, Extended Temperature Operation

Combination Modules

Function	Module	Description	Function	Module	Description
Combo	<u>CM4</u>	2 CH. 4 Ch. RS-422/485 ASYNC (TX±/RX±) & 12 Channel Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)	Combo	<u>CM8</u>	2 CH. Dual-redundant MIL-STD-1553 & 12 Channel Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)
	<u>CM5</u>	2 CH. Dual-redundant MIL-STD-1553 & 8 Channel ARINC 429/575, 100 KHz or 12.5 KHz, RX or TX, 256 Word Tx/Rx Buffer			

Architected for Versatility

NAI's Configurable Open Systems Architecture™ (COSA®) offers a choice of over 100 smart I/O, communications, or Ethernet switch functions, providing the highest packaging density and greatest flexibility of ruggedized embedded product solutions in the industry. Preexisting, fully-tested functions can be combined in an unlimited number of ways quickly and easily.

One-Source Efficiencies

Eliminate man-months of integration with a configured, field-proven system from NAI. Specification to deployment is a seamless experience as all design, state-of-the-art manufacturing, assembly and test are performed - by one trusted source. All facilities are located within the U.S. and optimized for high-mix/low volume production runs and extended lifecycle support.

Product Lifecycle Management

From design to production and beyond, NAI's product lifecycle management strategy ensures the long-term availability of COTS products through configuration management, technology refresh and obsolescence component purchase and storage.

All specifications are subject to change without notice. All product and company names are trademarks or registered trademarks of their respective holders

